WinTeK Sealing Industrial Co., Ltd.

ADDRESS: No.1-7, Shichuan Rd., Caotun Township, Nantou County 54254, Taiwan R.O.C TEL: +886 49 231-9788 FAX: +886 49 231-1388 E-MAIL: Service@wtk-sealing.com.tw. WEBSITE: www.wtk-sealing.com.tw.




TYPE: RE

RUBBER: NBR BLACK 80 SHORE A

FKM BROWN 80 SHORE A

METAL: SAE 1008 + CR3



RE

PN	ID	OD	Н
RE-10	10.0	24.0	2.5
RE-11	11.0	26.0	2.5
RE-12	12.0	26.0	2.5
RE-14	14.0	30.0	3.0
RE-15	15.0	30.0	3.0
RE-16	16.0	32.0	3.0
RE-17	17.0	32.0	3.0
RE-17	18.0	33.0	3.0
RE-20	20.0	35.0	3.0
RE-22	22.0	40.0	3.0
RE-24	24.0	40.0	3.0
RE-25	25.0	40.0	3.0
RE-26	26.0	40.0	3.0
RE-28	28.0	43.0	3.0
RE-30	30.0	47.0	3.5
RE-31	37.72	44.45	4.826
RE-32	32.0	49.0	3.5
RE-35	35.0	52.0	3.5
RE-38	38.0	55.0	3.5
RE-40	40.0	57.0	3.5
RE-40	41.0	57.0	3.5
RE-41	42.0	59.0	3.5
RE-42	45.0	62.0	3.5
RE-48	48.0	65.0	3.5
RE-40	50.0	70.0	4.5
RE-50	52.0	70.0	4.5
RE-52	55.0	75.0	4.5
RE-55	58.0	78.0	4.5
RE-60	60.0	80.0	4.5
RE-62	62.0	82.0	4.5
RE-65	65.0	85.0	4.5
RE-68 RE-70	68.0	88.0	4.5
KE-7U	70.0	90.0	4.5

PN	ID	OD	Н
RE-72	72.0	92.0	4.5
RE-75	75.0	95.0	4.5
RE-78	78.0	98.0	4.5
RE-80	80.0	100.0	4.5
RE-85	85.0	105.0	4.5
RE-90	90.0	110.0	4.5
RE-95	95.0	115.0	4.5
RE-100	100.0	120.0	4.5
RE-105	105.0	125.0	4.5
RE-125	125.0	148.0	4.5
RE-135	135.0	159.0	5.5
RE-225	225.0	250.0	6.5
	1	ı	