


WinTeK Sealing Industrial Co., Ltd.

ADDRESS: No.1-7, Shichuan Rd., Caotun Township, Nantou County 54254, Taiwan R.O.C
 TEL: +886 49 231-9788 FAX: +886 49 231-1388 E-MAIL: Service@wtk-sealing.com.tw
 WEBSITE: www.wtk-sealing.com.tw



TYPE: VA
MATERIAL: NBR BLACK 60 SHORE A
NBR BLACK 60 SHORE A (OZONE RESISTANCE)
FKM BROWN 60 SHORE A



PN	ID	OD	H
VA-003	2.5	5.5	3.0
VA-004	3.2	7.2	3.7
VA-005	4.0	8.0	3.7
VA-006	5.0	9.0	3.7
VA-007	6.0	10.0	3.7
VA-008	7.0	11.0	3.7
VA-010	9.0	15.0	5.5
VA-012	10.5	16.5	5.5
VA-013	11.7	17.7	5.5
VA-014	12.5	18.5	5.5
VA-016	14.0	20.0	5.5
VA-018	16.0	22.0	5.5
VA-020	18.0	26.0	7.5
VA-022	20.0	28.0	7.5
VA-025	22.0	30.0	7.5
VA-028	25.0	33.0	7.5
VA-030	27.0	35.0	7.5
VA-032	29.0	37.0	7.5
VA-035	31.0	39.0	7.5
VA-038	34.0	42.0	7.5
VA-040	36.0	46.0	9.0
VA-045	40.0	50.0	9.0
VA-050	45.0	55.0	9.0
VA-055	49.0	59.0	9.0
VA-060	54.0	64.0	9.0
VA-065	58.0	68.0	9.0
VA-070	63.0	75.0	11.0
VA-075	67.0	79.0	11.0
VA-080	72.0	84.0	11.0
VA-085	76.0	88.0	11.0
VA-090	81.0	93.0	11.0
VA-095	85.0	97.0	11.0
VA-100	90.0	102.0	11.0


PN	ID	OD	H
VA-110	99.0	113.0	12.8
VA-120	108.0	122.0	12.8
VA-130	117.0	131.0	12.8
VA-140	126.0	140.0	12.8
VA-150	135.0	149.0	12.8
VA-160	144.0	160.0	14.5
VA-170	153.0	169.0	14.5
VA-180	162.0	178.0	14.5
VA-190	171.0	187.0	14.5
VA-199	180.0	196.0	14.5
VA-200	180.0	210.0	25.0
VA-220	198.0	228.0	25.0
VA-250	225.0	255.0	25.0
VA-275	247.0	277.0	25.0
VA-300	270.0	300.0	25.0
VA-325	292.0	322.0	25.0
VA-350	315.0	345.0	25.0
VA-375	337.0	367.0	25.0
VA-400	360.0	390.0	25.0
VA-450	405.0	435.0	25.0
VA-500	450.0	480.0	25.0
VA-550	495.0	525.0	25.0
VA-600	540.0	570.0	25.0

WinTeK Sealing Industrial Co., Ltd.

ADDRESS: No.1-7, Shichuan Rd., Caotun Township, Nantou County 54254, Taiwan R.O.C
TEL: +886 49 231-9788 FAX: +886 49 231-1388 E-MAIL: Service@wtk-sealing.com.tw
WEBSITE: www.wtk-sealing.com.tw



TYPE: VL
MATERIAL: NBR BLACK 60 SHORE A
NBR BLACK 60 SHORE A (OZONE RESISTANCE)
FKM BROWN 60 SHORE A



PN	ID	OD	H
VL-110	99.0	112.0	10.5
VL-120	108.0	121.0	10.5
VL-130	117.0	130.0	10.5
VL-140	126.0	139.0	10.5
VL-150	135.0	148.0	10.5
VL-160	144.0	157.0	10.5
VL-170	153.0	166.0	10.5
VL-180	162.0	175.0	10.5
VL-190	171.0	183.0	10.5
VL-200	182.0	194.0	10.5
VL-220	198.0	210.0	10.5
VL-250	225.0	237.0	10.5
VL-275	247.0	259.0	10.5
VL-300	270.0	282.0	10.5
VL-325	292.0	304.0	10.5
VL-350	315.0	327.0	10.5
VL-375	337.0	349.0	10.5
VL-400	360.0	372.0	10.5
VL-425	382.0	394.0	10.5
VL-450	405.0	417.0	10.5
VL-500	450.0	462.0	10.5
VL-525	472.0	484.0	10.5
VL-550	495.0	507.0	10.5
VL-600	540.0	552.0	10.5