


WinTeK Sealing Industrial Co., Ltd.

ADDRESS: No.1-7, Shichuan Rd., Caotun Township, Nantou County 54254, Taiwan R.O.C
 TEL: +886 49 231-9788 FAX: +886 49 231-1388 E-MAIL: Service@wtk-sealing.com.tw
 WEBSITE: www.wtk-sealing.com.tw



TYPE: RE
RUBBER: NBR BLACK 80 SHORE A
 FKM BROWN 80 SHORE A
METAL: SAE 1008 + CR3



RE

PN	ID	OD	H
RE-10	10.0	24.0	3.5
RE-11	11.0	26.0	3.5
RE-12	12.0	26.0	3.5
RE-14	14.0	30.0	4.0
RE-15	15.0	30.0	4.0
RE-16	16.0	32.0	4.0
RE-17	17.0	32.0	4.0
RE-18	18.0	33.0	4.0
RE-20	20.0	35.0	4.0
RE-22	22.0	40.0	4.0
RE-24	24.0	40.0	4.0
RE-25	25.0	40.0	4.0
RE-26	26.0	40.0	4.0
RE-28	28.0	43.0	4.0
RE-30	30.0	47.0	4.5
RE-32	32.0	49.0	4.5
RE-35	35.0	52.0	4.5
RE-38	38.0	55.0	4.5
RE-40	40.0	57.0	4.5
RE-41	41.0	57.0	4.5
RE-42	42.0	59.0	4.5
RE-45	45.0	62.0	4.5
RE-48	48.0	65.0	4.5
RE-50	50.0	70.0	5.5
RE-52	52.0	72.0	5.5
RE-55	55.0	75.0	5.5
RE-58	58.0	78.0	5.5
RE-60	60.0	80.0	5.5
RE-62	62.0	82.0	5.5
RE-65	65.0	85.0	5.5
RE-68	68.0	88.0	5.5
RE-70	70.0	90.0	5.5

PN	ID	OD	H
RE-72	72.0	92.0	5.5
RE-75	75.0	95.0	5.5
RE-78	78.0	98.0	5.5
RE-80	80.0	100.0	5.5
RE-85	85.0	105.0	5.5
RE-90	90.0	110.0	5.0
RE-95	95.0	115.0	5.5
RE-100	100.0	120.0	5.5
RE-105	105.0	125.0	5.5
RE-125	125.0	148.0	5.5
RE-135	135.0	159.0	6.5
RE-225	225.0	250.0	7.5